

SM-05 Hybrid LED Street Light

Product Description

SM-05 Hybrid LED Street Light is in an off-grid hybrid outdoor led lighting system that eliminates the reliance on power grids that conventional street lighting systems have. SM-05 Hybrid LED Street Lights are not only able to generate power from solar energy in the daytime, but also generates the power from wind. These SM-05 Hybrid LED Street Lights are very cost effective and really easy to install. It will be configured according to the environmental conditions of the installation site as well as your specific requirements. The lighting from SM-05 Hybrid LED Street Lights System lasts more than 10 hours per night, that's why demand for this product is really high due to both its effectiveness and efficiency.

Benefits of Hybrid LED Street Light:

- 1. Solar wind hybrid lighting system is an off-grid outdoor lighting system that is cost effective and simple to install almost anywhere with good sunshine and wind condition
- 2. Environment-friendly, energy-saving, long lifespan.
- 3. Easy installation, Free-maintenance
- 4. Low-voltage, safe and reliable
- 5. Water proof of IP65, avoid water vapor or corrosive gas erosion of chips and circuit boards.
- 6. Competitive for its outstanding working ability against harsh environments such as heavy rain, low temperature, and so on.



Detailed Parameters:

No	Item	Picture	Parameters
1	SM-05	The same of the sa	Power:20w/30w/40w/50w/60w/80w/100w
	Led		Chip: Philips/ Bridgelux/Cree/ Epistar
	Lamp		Lumens:90lm/w
			Voltage:DC12V/24V
			Color temperature:3000-6500K
2	2 Solar		Power:40w/60w/2*40w/2*50w /2*60w/2*80w/2*100w
Panels	Panels		Nominal Voltage:18V
			Efficiency of solar cells:18%
			Material: Mono Cells/Poly Cells
3	Battery	a disease	Capacity:38AH/65AH/2*38AH/2*50AH/2*65AH/
		a source	2*90AH/2*100AH
			Type: lead-acid
			Nominal Voltage:12V/24V
4	Battery		Material: Plastics
	Вох		IP Rating:IP67
5	Controll		Rated Current:5A/10A/15A/20A
	er	-	Nominal Voltage:12V/24V
6	Pole		Height: 5m(A); Diameter: 90/140mm(d/D); Thickness:
			3.5mm(B);Flange Plate:240*12mm(W*T)

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com




-	1	<u> </u>	,
		*	Height: 6m(A); Diameter: 100/150mm(d/D); Thickness:
			3.5mm(B);Flange Plate:260*12mm(W*T)
			Height: 7m(A); Diameter: 100/160mm(d/D); Thickness:
			4mm(B);Flange Plate:280*14mm(W*T)
			Height: 8m(A); Diameter: 100/170mm(d/D); Thickness:
			4mm(B);Flange Plate:300*14mm(W*T)
			Height: 9m(A); Diameter: 100/180mm(d/D); Thickness:
		ı	4.5mm(B);Flange Plate:350*16mm(W*T)
			Height:10m(A); Diameter: 110/200mm(d/D); Thickness:
			5mm(B);Flange Plate:400*18mm(W*T)
7	Anchor	1	4-M16; 4-M18; 4-M20
	Bolt	M	
8	Cables		18m/21m/24.6m/28.5m /32.4m/36m/
9	Wind		100w wind turbine for 20w/30w/40w led lamp.
	Turbine	20	Rated Voltage:12/24V
			Packing Size:470*410*330mm
			Security Wind Speed:35m/s
			Weight:14Kg
			300w wind turbine for 50w/60w/80w/100w led lamp.
			Rated Voltage:12/24V
			Security Wind Speed:35m/s

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com




	G.W:18Kg
	3

Product Display:



Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com









Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com





Install the product in place with good sunshine and wind condition to display the function of the product