

SM-T1R LED Street Light

Product Description

SM-T1R LED Street Light is better than normal LED lights for its large number light sources. Which can be different with specific model and enables different light intensity. Also, with the help of its advanced chip, the speed of it to emit light would be much better than other LED street lights in the market. And the color rendering index of SM-T1R LED Street Light is higher than many other lights, helping drivers to identify the different signs correctly and reduce the incidence of traffic accidents effectively. What's more, SM-T1R LED Street Light is competitive for its outstanding working ability against harsh environments such as heavy rain, low

SM-T1R LED Street Light Features

temperature, and so on.

- 1. All metal structure, built-in driver,
- 2. Double-coupling IP68 protection for optics set, highest waterproof level,
- 3. Photocontrol equipped for better energy-saving performance,
- 4. Ergonomic lighting distribution to achieve uniform illuminating effect,
- 5. Eutectic soldering without wire bonds to avoid lighting failure

Detailed Parameters



Zhejiang seming zhedrome con, zha													
Input		Power		Power		Junction		CRI		Working		Storage	
Voltage		Efficiency		Factor		Temperature				Environment		Temperat	
												ure	
AC100V-		85%(9W)		0.95(9W)		<80℃		Ra≥70		-40 ℃ ~+50 ℃		-40	$^{\circ}\!\mathbb{C}$
240V		88%(16W)		0.98(16W)						10%~90%RH		~+50°C	
LED Life		Surge		ССТ		LED Brand		Installation		Material		IP Rating	
span		Protection						Diameter					
>60000Ho		10KV		3000К,		Lumileds		38~45mm		Metal		Optical	
urs				4000K,								set If	P68,
				5000K,								Whole	
				5700K								Fixture	
												IP67	
Mode	de Syst		LM/W	LM/W	Initial		Initial	Produ	Pack	aging	N.W.	G.W.	
1	Pov	wer (Ultra		(High)	Lu	men	Lumens	ct Size	dimension		(Kg)	(Kg)	
			High)		s(Ultra		(High)	(mm)	(mm)				
					Hi	gh)							
SM-	9		110	100	990		900	340*8	410*150*1		0.7	0.9	
T1R								0*70	40				
	16	110		100	17	60	1600	340*8	410*150*1		0.7	0.9	
								0*70	0 40				
					_	·							_

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com




Product Display





[Lighting Distribution Curve]



T2L2207
IESNA Type II Long



Application

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, **WhatsApp:** +8618267537265; **Email:** sales@seminglighting.com