

SM-T31A LED Street Light

Product Description

SM-T31A LED Street Light is better than normal LED lights for its large number light sources. Which can be different with specific model and enables different light intensity. Also, with the help of its advanced chip, the speed of it to emit light would be much better than other LED street lights in the market. And the color rendering index of SM-T31A LED Street Light is higher than many other lights, helping drivers to identify the different signs correctly and reduce the incidence of traffic accidents effectively. What's more, SM-T31A LED Street Light is competitive for its outstanding working ability against harsh environments such as heavy rain, low temperature, and so on.

SM-T31A LED Street Light Features

- 1. Modular pluggable technology, tool-free onsite maintenance,
- 2. Honeycomb briquette burning effect and the whole structure cooling technology,
- 3. Double-coupling IP68 protection, highest waterproof level,
- 4. Metal structure, high mechanical strength,
- 5. Intelligent constant current driving technology, long life span,
- 6. Ergonomic light distribution to achieve uniform illuminating effect,
- 7. Free modular serialization and full power range solutions.

Detailed Parameters



Input	Power	Power		Junction		CRI	Working		Storage	
Voltage	Efficiency	Factor		Temperature			Environment		Temperat	
									ure	
AC100V-	91%	0.95		<80℃		Ra≥70	-40 °C ~+50 °C		-40	$^{\circ}\!\mathbb{C}$
277V							10%~90%RH		~+50	o℃
LED Life	Surge	ССТ		LED Brand		Installati	Material		IP Rating	
span	Protection			<u> </u>		on				
						Diamete				
						r				
>60000Ho	10KV/5KA	3000K,		Lumileds		57~63m	Metal LED			
urs		4000K,				m			Module	
		5000K,							IP68),
		5700K							Power	
									supply	
									IP67	
Model	System	LM/	LM/	Initial	Initial	Product	Packaging	N.	W.	G.W.
	Power	W	W	Lumen	Lumen	Size (mm)	dimension	(K	g)	(Kg)
		(Ultr	(High	s(Ultra	S		(mm)			
		а)	High)	(High)					
		High)								

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com



			8 ~		5				
SM-T31A-2	80	160	120	12800	9600	395*300*	480*385*	5.2	5.9
						90	165		
	100	155	115	15500	11500	395*300*	480*385*	5.2	5.9
						90	165		
	120	150	110	18000	13200	395*300*	480*385*	5.2	5.9
						90	165		
SM-T31A-3	120	160	120	19200	14400	475*300*	560*385*	6.0	7.1
						90	165		
	150	155	115	23250	17250	475*300*	560*385*	6.0	7.1
						90	165		
	180	150	110	27000	19800	475*300*	560*385*	6.0	7.1
						90	165		
SM-T31A-4	160	160	120	25600	19200	555*300*	640*385*	6.8	8.2
						90	165		
	200	155	115	31000	23000	555*300*	640*385*	6.8	8.2
						90	165		
	240	150	110	36000	26400	555*300*	640*385*	6.8	8.2
						90	165		
SM-T31A-5	200	160	120	32000	24000	655*300*	740*385*	7.8	9.4
						90	165		
	250	155	115	38750	28750	655*300*	740*385*	7.8	9.4

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com



 •	 \mathcal{O}	,		/	
			00	1.00	
			90	102	

Product Display






(E CB RoHS

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 8267537265, WhatsApp: +8618267537265; Email: sales@seminglighting.com



[Lighting Distribution Curve]



Application

