



## SM-85 Monocrystalline Solar Panel

### Product Description

Now, SM-85 Monocrystalline Solar Panels have becoming more and more popular with our customers as it have the highest efficiency rates since they are made out of the highest-grade silicon. The efficiency rates of these solar panels are typically 15-20%, which up to four times the amount of electricity as thin-film solar panels. Since these SM-85 Monocrystalline Solar Panels yield the highest power outputs, they require the least amount of space compared to any other types. What's more, SM-85 Monocrystalline Solar Panels live the longest and will save lot of your time to replace it. Also, it tend to perform better than similarly rated polycrystalline solar panels at low-light conditions. As a conclusion, SM-85 Monocrystalline Solar Panels is the best choice for you.

### Features:

- High conversion efficiency.
- Low power tolerance of 0~+3%.
- Low degradation under light exposure.
- Can withstand high wind-pressure, snow load and extreme temperature.
- Passing IEC61215 2400Pa mechanical load test.

### Benefits of Monocrystalline Solar Panel:

- Monocrystalline Solar Panels have the highest efficiency rates since they are made out of



# Zhejiang Seming Electronic Co., Ltd

the highest-grade silicon. The efficiency rates of Monocrystalline Solar Panels are typically 15-20%. Monocrystalline Solar Panels produce up to four times the amount of electricity as thin-film solar panels.

- Monocrystalline Solar Panels are space-efficient. Since these solar panels yield the highest power outputs, they also require the least amount of space compared to any other types.
- Monocrystalline Solar Panels live the longest. Most solar panel manufacturers put a 25-year warranty on their Monocrystalline Solar Panels.
- Tend to perform better than similarly rated poly panels at low-light conditions.

## Detailed Parameters:

Model Type	SM-85
Dimensions	905*668*35
Peak Power(Pmax)	85
Maximum Power Voltage(Vmp)	18.25
Maximum Power Current(Imp)	4.68
Open Circuit Voltage(Voc)	21.90
Short Circuit Current(Isc)	5.15
Cells Efficiency(%)	16.98
Module Efficiency(%)	14.06
Maximum System Voltage(V)	1000
Maximum Series Fuse Rating(A)	15

Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 5258532577, **WhatsApp: +8615258532577**; **Email: [sales@seminglighting.com](mailto:sales@seminglighting.com)**



# Zhejiang Seming Electronic Co., Ltd

Power Tolerance	0~+3%
Pmax Temperature Coefficients(W/°C)	-0.450%
Voc Temperature Coefficients(V/°C)	-0.350%
Lsc Temperature Coefficients(A/°C)	+0.040%
NOCT Nominal Operating Cell Temperature(°C)	47 ± 2
Operating and Storage Temperature(°C)	-40~+85
Standard Test Conditions(STC)	1000W/m <sup>2</sup> , AM1.5; 25+/-2°C
Warranty on product materials and processing	10 years
Power output warranty	10years:90%,25years:85%
Certifications	TUV、CE、CQC、UL
Products Certifications	IEC61215、IEC61730、MCS CEC
Factory Certifications	ISO9001:2008、ISO14001、ISO18001

Product Display:



# Zhejiang Seming Electronic Co., Ltd



Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 5258532577, **WhatsApp: +8615258532577**; **Email: [sales@seminglighting.com](mailto:sales@seminglighting.com)**



# Zhejiang Seming Electronic Co., Ltd

---



Address: Haicheng Road, Baiguan Industrial District, Shangyu Area, Shaoxing City, Zhejiang province, China; Tel: +861 5258532577, **WhatsApp: +8615258532577**; **Email: [sales@seminglighting.com](mailto:sales@seminglighting.com)**



Application:

- On-grid residential roof-tops.
- On-grid commercial/industrial roof-tops
- Solar power plants
- Off-grid system
- Other on-grid applications